



PURE ACRYLIC WATERBASED COATINGS TECHNICAL DATA SHEET

GLAZE COAT

PRODUCT DESCRIPTION

Prodec Glazecoat is an innovative waterbased, clear coating. It is used as a sealer for waterbased paint-coated surfaces to protect substrates and minimise dirt collection.

PRODUCT FEATURES

- Impedes dirt collection
- Excellent adhesion to waterbased coatings
- Improves film hardness, abrasion/weather resistance and ability to be cleaned

APPLICATION AREAS

- On sound, clean waterbased/emulsion paint coatings

SURFACE PREPARATION

- Remove all loose, flaking or bubbling paint. Remove all dust, foreign material or fungal and algal growth.

APPLICATION PROCEDURE

- Stir well before use
- Use a brush or roller to apply a generous coat of Prodec Glaze Coat
- Allow 4-6 hours to dry before recoating
- Use a brush or roller to apply a further generous coat

GENERAL

- Do not apply before 9 am or after 4 pm in winter.
- Prodec Glazecoat is ready for use unthinned. Thinning will reduce its.
- For best results use 2 coats of Prodec Glazecoat.
- The spreading rate will vary with porosity and type of substrate. For uncoated new work 1 litre will cover about 8-10m². For subsequent coats and when applied to sealed or previously painted substrates, 1 litre will cover 10-12m².
- Clean application equipment with clean tap water.

COLOUR RANGE AND QUANTITIES

- Available in clear
- 1/5 litres

PRECAUTIONS

- Ensure there is adequate ventilation during application.
- Seek medical advice if swallowed. Do not induce vomiting.
- In case of contact with eyes, rinse with plenty of clean water
- Keep out of reach of children.
- Full Material Safety Data Sheet available at www.prodecpaints.co.za