



WATERBASED COATINGS TECHNICAL DATA SHEET

SUPER ACRYLIC

PRODUCT DESCRIPTION

Prodec Super Acrylic is a high quality, waterbased, matt coating for areas that need a durable coating.

PRODUCT FEATURES

- Durable
- Easy to clean
- High opacity/hiding power
- Low odour
- Good adhesion
- Easy application
- Estimated Dry Film Thickness: 40-50 Microns per coat when applied at 8m²/L
- Prodec 5 Year Quality Warranty (for interior use only) (Subject to terms and conditions available at www.prodecpaints.co.za).

APPLICATION AREAS

- Plaster, hardboard and fibre-cement walls
- Primed metal and wooden substrates

SURFACE PREPARATION

- **Uncoated concrete surfaces:** remove all dust, foreign material or fungal and algal growth. Fill and seal all visible cracks and coat with Prodec Plaster Primer.
- **Uncoated weathered or new fibre-cement surfaces:** remove all dust, foreign material or fungal and algal growth and, if friable or powdery, seal with Prodec Bonding Liquid.
- **Raw Plaster:** remove all dust, foreign material or fungal and algal growth. Fill and seal all visible cracks.
- **Previously Painted Surfaces:** remove all loose, flaking or bubbling paint; remove all dust, foreign material or fungal and algal growth. Allow to dry. If then powdery or friable, seal with Prodec Bonding Liquid.

APPLICATION PROCEDURE

- Always stir well before use
- Use a brush, roller or airless spray to apply a generous coat of Prodec Super Acrylic
- Allow 4-6 hours to dry before recoating
- Apply a second generous coat with a brush, roller or airless-spray

GENERAL

- Do not apply before 9 am or after 4 pm in winter.
- Do not apply to exterior surfaces if rain is likely within 4-6 hours of application.
- Prodec Super Acrylic is ready for use unthinned. Thinning will reduce its hiding power.
- For best results use 2 coats of Prodec Super Acrylic.

- The spreading rate will vary with porosity and type of substrate. For uncoated new work 1 litre will cover about 6-8m². For subsequent coats and when applied to sealed or previously painted substrates, 1 litre will cover 8-10m².
- Clean application equipment with clean tap water.

COLOUR RANGE & QUANTITIES

- Tint Bases: Pastel, *Deep, *Transparent (*Only available in KZN)
- Available in white, black and pastel shades
- 1/ 5/20 litres

PRECAUTIONS

- Ensure there is adequate ventilation during application.
- Seek medical advice if swallowed. Do not induce vomiting.
- In case of contact with eyes, rinse with plenty of clean water
- Keep out of reach of children.
- Full Material Safety Data Sheet available at www.prodecpaints.co.za